

## Solutions 8

**Exercise 8.1.** First a sanity check: the dimension is  $k$  in both cases. Moreover, the minimum distance of the RS code is  $q - k$ , and the minimum distance of the code viewed as a BCH code is at least  $q - k$  by the BCH bound.

Let  $f(x) = \sum_{l=0}^{k-1} f_l x^l$  be a message. The corresponding codeword is

$$c = (f(\alpha^0), \dots, f(\alpha^{q-2})).$$

Another way to view  $c$  is as a polynomial  $c(x) = \sum_{i=0}^{q-2} f(\alpha^i) x^i$ . It is enough to prove that any such codeword is a multiple of  $g(x)$ , i.e., that

$$c(\alpha^j) = 0, \quad j = 1, \dots, q - 1 - k.$$

Now

$$\begin{aligned} c(\alpha^j) &= \sum_{i=0}^{q-2} f(\alpha^i) (\alpha^j)^i \\ &= \sum_{i=0}^{q-2} \sum_{l=0}^{k-1} f_l (\alpha^i)^l (\alpha^j)^i \\ &= \sum_l f_l \sum_i (\alpha^{j+l})^i. \end{aligned}$$

Note that  $j$  ranges over  $1, \dots, q - 1 - k$  and  $l$  ranges over  $1, \dots, k - 1$ , so that  $0 < j + l < q - 1$  and thus  $\alpha^{j+l} \neq 1$  for all values of  $j$  and  $l$ . Moreover, for fixed  $j$  and  $l$ ,  $(\alpha^{j+l})^{q-1} = 1$ , or in other words,

$$(\alpha^{j+l} - 1) \sum_{i=0}^{q-2} (\alpha^{j+l})^i = 0.$$

But since  $\alpha^{j+l} \neq 1$ , we have that

$$\sum_{i=0}^{q-2} (\alpha^{j+l})^i = 0$$

and thus  $c(\alpha^j) = 0$ .

**Exercise 8.2.**

1. Let  $D$  be the dual code of  $\text{GRS}_{n-1}(\alpha, v)$ .  $D$  has dimension 1 and thus consists of all scalar multiples of some fixed vector  $v' = (v'_1, \dots, v'_n)$ . We must show that all  $v'_i$  are nonzero. Now by the dual code property, and taking a basis for  $\text{GRS}_{n-1}(\alpha, v)$  corresponding to the basis of polynomials  $\{1, x, \dots, x^{k-1}\}$ , we know that  $v'$  satisfies

$$\begin{aligned} v_1 v'_1 + \dots + v_n v'_n &= 0 \\ \alpha_1 v_1 v'_1 + \dots + \alpha_n v_n v'_n &= 0 \\ &\vdots \\ \alpha_1^{n-2} v_1 v'_1 + \dots + \alpha_n^{n-2} v_n v'_n &= 0. \end{aligned}$$

This is equivalent to saying that

$$\begin{pmatrix} 1 & 1 & \dots & 1 \\ \alpha_1 & \alpha_2 & \dots & \alpha_n \\ & \vdots & & \\ \alpha_1^{n-2} & \alpha_2^{n-2} & \dots & \alpha_n^{n-2} \end{pmatrix} \begin{pmatrix} v_1 v'_1 \\ v_2 v'_2 \\ \vdots \\ v_n v'_n \end{pmatrix} = 0. \quad (1)$$

If any  $v'_i$  was equal to 0, then equation (1) gives a set of simultaneous equations for the other  $v_i v'_i$  whose coefficient matrix is Vandermonde. But then all  $v_i v'_i$  must be 0 and hence all  $v'_i$  must be 0, which is impossible since the space generated by  $v'$  is of dimension 1. Hence  $D$  is indeed  $\text{GRS}_1(\alpha, v')$ .

2. A basis for  $\text{GRS}_k(\alpha, v)$  is

$$\{(\alpha_1^s v_1, \alpha_2^s v_2, \dots, \alpha_n^s v_n)\}_{s \leq k-1},$$

and a basis for  $\text{GRS}_{n-k}(\alpha, v')$  is

$$\{(\alpha_1^t v'_1, \alpha_2^t v'_2, \dots, \alpha_n^t v'_n)\}_{t \leq n-k-1}.$$

A necessary and sufficient condition for duality is to have

$$\sum_{i=1}^n (\alpha_i^s v_i)(\alpha_i^t v'_i) = 0$$

for all  $s, t$  as specified above. But

$$\sum_{i=1}^n (\alpha_i^s v_i)(\alpha_i^t v'_i) = \sum_{i=1}^n \alpha_i^{s+t} v_i v'_i = 0$$

for  $s + t \leq n - 2$ , by equation (1).

Thus we see that in particular, the dual of a RS code is a GRS code.

### Exercise 8.3.

1. Suppose that there is a codeword  $c$  of weight less than  $k$ . Project the code to the subset of the coordinates determined by the nonzero positions of  $c$ . No two codewords can have the same projections, since otherwise, their difference will be all zeros at the nonzero positions of  $c$  and this will violate the ZDF property of the code. But this gives a contradiction as there are  $q^k$  codewords and their projection to less than  $k$  coordinates cannot be injective. Thus the minimum distance of the code is at least  $k$ .
2. As the code is *MDS* the distance  $d$  of the code is equal to  $n - k + 1$ . Moreover we know that  $d \geq k$ , which means  $k \leq (n + 1)/2$ . Thus  $d \geq n - (n + 1)/2 + 1 = (n + 1)/2 > n/2$ , and the weight of all nonzero codewords is larger than half the code length. Therefore, the code is *ZDF* as for every pair of codewords there has to be a position where both words are nonzero.